

## EFFICIENT SMART CITY GARBAGE COLLECTION METHODOLOGY USING MOTH FLAME OPTIMIZATION

**Kavitha.R<sup>1</sup>, Sumathi.P<sup>2</sup>**

<sup>1</sup> *Research Scholar/PG & Research Department of Computer Science,  
Government Arts College*

*Coimbatore-18. INDIA. Email -[rkkavitha1989@gmail.com](mailto:rkkavitha1989@gmail.com)*

<sup>2</sup> *Assistant Professor/PG & Research Department of Computer Science,  
Government Arts College  
Coimbatore-18. INDIA.*

**Abstract:** This paper evaluates the features affecting disposal of garbages in varied places and provokes an estimable algorithm to enhance in an effective manner. The aim of the research is to effectively manage the garbage disposal by minimum consumption of resources using Moth Flame Optimization algorithm. It analysis the effective collection of urban garbage by overcoming the entire defect occurred in existing system. For implementation of the technique, consider the system in bidirectional decision making based on the difficulties. While designing, certain criterias are deliberated such as intermediary shift, reduction of cost, locating shortest distance. The output suggests that there is a wide scope in garbage collection routing process to detect the intuitions. The analysis describes that the approached system will be definitely promotes a reliable garbage management in future.

**Keywords:** Moth Flame Optimization algorithm, Garbage Collection, Garbage Management.

### 1. Introduction:

Due to the immense population urban waste generation gets increased from 11 to 30 %. Anything that is recognized as unwanted is considered as garbage. It creates a lot of harmful factors to the environment such as air pollution; many younger and older peoples get affected. In the developing era, most of the people are highly fighting for the economy. So they failed to manage the amount of garbage they created. It has not been maintained properly. Population explosion gets highly tied up with the lifecycle of both village and city. In village side, the people produce easily degrading products whereas, in

city side not easily degrading materials are handled like polythene bags etc. Hence it becomes a quite complex process for the municipal associations to handle such garbage in an effective manner. On collecting such garbage, certain creative transport methodologies are handled to promote cost effective, consumption of time.

To promote the flexibility in garbage disposal, the municipality corporation should enhance the approach at the local region for disposing of trash than collection of large regional garbage. Current methodologies of waste disposal are more complex to implement in real time, as it needs more number of vehicles, large number of trash containers are required at each node for collection. To improve the method to be effective in some aspects like reduction in cost, enhancing collecting techniques, tenability etc. From early 1970s, certain schemes are undertaken to promote for the garbage collective method. There will be problems raised due to the coverage problem of garbage collection. A previous study includes the decision handling process in terms of technology, surrounding structure and financial resources. But it does not mean the complex nature of collection of garbage in the collecting environment. Only few of

them describe the concern in garbage separating and recycle process for the result of flexibility. The global nature promotes that certain technology will be embedding in future such as GPS system for smart detection of the garbage collecting vehicle and also tracks the most garbage present area.

This research provides an upgrade scheme that follows bidirectional choice of waste collection to enhance the effectiveness and reduce the complex nature of the regional. This process promotes a better reliable smart solution to garbage disposal in future. The loyalty of the paper is to inclusive of multi terminal route and multi compartment vehicle route using roll on roll off strategy scheme. It definitely becomes a collaborative methodology for the smart area in future generation. This scheme promotes not only divided collection and disposal of garbage but also enhances the travelling efficiency divided collection and disposal of garbage but also enhances the travelling efficiency.

## 2. Literature Review:

Ghose et al. [9] proposed GIS based waste collection method. It includes the promotion in plan with respect to number of containers, vehicles etc. Using satellite information, the road routing, location of trash, disposing area are gets detected. Based on the area located and garbages, three types of containers are designed. Hence at the time of collecting trashes, three vehicles are designed to handle the three types of bins. It reduces the pickup time at varied locations to decrease the vehicle requisites. The system manages the fuel usage and balancing the load in the containers.

The fuel usage while collecting the wastes in region and its surrounding impacts [10]. Conceptual algorithm is suggested that includes the collection of garbage from the place to the disposing area. It fully controlled with respect to the driver, calculates the trashes undertaken in the day, amount of fuel usage, number of area and trips handled on the considered day etc. It handles an application that interprets the amount of fuels spent for the trash undertaken.

Mohanty.B explained the planning of improvement in collection of garbage in a shortest distance and scheduled algorithm [16]. For the prior 15 years, there have been a revolution took place between the private and public sectors to introduce new technologies such as routing application tool to enhance the garbage collective process. The trashes are separated in accordance to more priority and less priority and it is based on the last collected day. In this shortest distance are calculated with reference to dijkstra algorithm [17]. It suggests the shortest track between the start and end node by considering each terminal as starting point thereby finds the nearest node. After gathering all the data, the routing duration are estimated using GPS.

The exploded effect of vehicles in the consideration of various garbage collection methods from a certain region [12]. Describes two set of routes namely arc routing to visit a several roads in the regions and node routing to travel set of terminals in the particular road. When the vehicle gets full of trashes in node routing, then it returned to the disposal area to dispatch it hence the existing area affected. For every time, visiting the disposing area, the duration gets enhanced and only few of the areas get visited. A survey resulted that round layout architecture, the distance travelled increased with reduction in time. As a result, it is concluded that all the methods included enhances the collection strategy and reduces the resource management.

The framed suggested route using ant colony procedure for managing the waste collection method [11]. It is based on geographical information system analysis. It analysis all the requisite data for effective management of waste like number of garbage bins, population, path traffic, vehicle capacity etc. The algorithm used to monitor, validate and test the method of implementation of garbage management with other existing systems. It finds a better settlement to the problems that have been arisen. When a list is promoted for collection of garbage, the vehicle wants to visit the entire person under listed otherwise they will be penalised. As a result, it ensures that it could take minimum route and cost in collecting the wastes.

The collection and transfer of the wastes to reduce global warming. To secure the survival of humans, the waste generated must be transferred to a separate area for disposal. The mode of transport can be of train, truck, ships etc. The transfer of trashes defines the mode of loading from one mode to another mode for the benefit of reducing the consumption [6]. If the disposing area is too long distance and with the usage of intermediate stations the transfer of wastes are carried out to enhance the collection of garbage.

The routing problem caused when collecting the garbages. It is depending upon the duration limit to promote the cost effective. It loads all the trashes at the disposal site and should be empty when arrives at the stopping end [4]. Visit to the customer must be done atleast once within the time limit. It does not affect the break time of the employees and it is separated from the collection period. Framed certain techniques for collective methods of garbages in dense city areas [8]. To justify the process, one must know about the volume of trashes in the bin and the vehicle for effective transformation.

The Geographical information system exploded based module for collection of waste. Every vehicle must visit all the bin trash in accordance to reduce the fuel consumption, other resources and emission of gases. GIS is used to manage the technological improvement towards garbage management [5].

Garg and Gupta [7] researched that moth flame optimization technique for detecting shortest path between the initial and beginning node. It promotes a network that makes the individuals to share the information between the nodes. It depends upon certain parameters like time or delay extent. It proposed a method that avoids the long haul and finds the shortest distance. It believed that the system reduces the resources usage and exploded a cost-effective method for enhancement of network communication.

The Moth Flame Optimization promotes for utilizing in the field of sensor terminal deployment, terminal locating, message passing etc. Suggested that the optimization is transverse in deployment and it maintains a fixed angle to the direction [21]. The usage of this optimization in wireless systems is to decrease the terminals in the track by correlating to enhance the coverage distance by reducing all the defects occurred and finds the best solution for the necessary problem.

To train multiple perceptrons in moth flame optimization by evaluating the locally occur problems and the results are compare with other already existing techniques [22]. It notifies that the algorithm promotes best performance in all the criteria. The MFO is highly accurate to convergence rate and possess best optimization ability. It reduces all the errors that have occurred under the application [18].

### **3. Motivation of the Research**

The motto of the Research is to provide green smart localised environment in considering cost effective consequences. Collection of wastes is a well-organized form to attain the effective way.

Heuristic procedure is defined as the efficient approach of promoting better solutions to the way of process but is not ensure that accurate results are found. It finds a closest solution to the problems, rather than promoting accuracy. Tabu [8] search is referred as the location of nearest route for the problem raised but is not suitable when the process is done on the suboptimal regions. It solves mostly for local search problem. Many procedural algorithms are considered to solve numerous solutions but all of them having certain limitations. Some of the algorithms are formulated as follows:

### **3.1.1 Genetic algorithm**

Genetic algorithm is an approach that uses naturally selection of ranges and approached for high quality searching problem [1]. It includes the operation such as cross over, transition. Thereby transforms one path to another by finding alternative track. The solution is depicted in the form of zeros and ones. The process starts from the sequentially generated population, once it is defined the fitness range are defined and the operation takes place like alteration, crossover etc. It finds out better quality if the population rate is so small. It does not used often as it has certain limitations like fitness range updation is not processed for complex process, it does not work well with complexity, not finds solution for global problems, doesn't function appropriately with dynamic data range and it promotes programs for functioning of task using genetic programming [2].

### **3.1.2 Particle Swarm Optimization**

Another algorithm called as Particle Swarm Optimization is a computational process that uses velocity and exact position of the location by iteration process. The motion is processed by accurate position of particle and it has being used for multiple approaches at the same time. Few or no assumptions will be carried out for large space solutions. It took majority to find best solution for continual nonlinear process [12]. It has a consequence on process performance. It wants to be tuned by another optimizer and it does not use velocity for speed up acceleration. It is widely employed in robotics for alarm purpose.

### **3.1.3 Ant colony Optimization**

It is a procedure that promotes best route by using graphs. Vehicle route and internet route took place a majority in this algorithm through graph. The swarm intellectual approach that uses idea from the ants. When an ant promotes a best route in searching the food, all other ants will follow the same route[2]. It took a best solution for problems raised. It has been applicable to parallel implementations and multiple destination searching. It has been implemented as it must visit the destination once in exact, distance route has less priority in choosing. The shortest route is finding out by the combination of several paths [11].

### **3.1.4 Evolution strategy**

Evolution strategy is an optimization strategy that depends on processing. It follows certain strategy like alteration, selection etc. It depends upon evolutionary or artificial computational process [21]. Most vital work has been developed for find out best route for the collection of garbage for the first without misleading. It is mostly based on the distance and power needed for the travel from one end to another end by choosing best route, elements such as delay and ambiguous route can confuse the appropriate route forwarding. When the shortest route is determined, the way of travel towards collecting is maintained. In this if a best route does not determined then the updation takes place to find the best solution. The priority of collection is based on their fitness range [20].

#### 4. Heuristic for MCMC-RORO Algorithm

The Existing MCMC-RORO algorithm finds the nearest node after collecting garbage from certain node or otherwise it finds intermediate node for disposing all the garbage collected and finds the next node if time is available. It consumes more time if large number of nodes are present. Hence it is a disadvantage in the system. Hence it promotes numerous cycles to find out the intermediate node for unvisited node. [15] explores that MFO is tested on 29 operations and it promotes a well-defined process in all the criteria considered.

#### 5. Heuristic for MFO algorithm

Moth flame optimization is a newly introduced methodology based on operation of moth flies and it is a population based procedure. The advantages of existing system over this algorithm are it does not require separate mechanism for both Tabu route and updation of every process [7]. Moth flies travels towards the light by maintaining fixed angle in three dimensional aspects. It is contrasted to the algorithm that the moths are considered as the vehicles and the position represents the directions of travel [15]. The moths are attracted towards the flame, in the research the vehicles are travelled towards the path of collecting the garbage. The route direction can be changed at any time according to the necessity. It is mainly applicable for load disposal and economic disposal due to the promote of best outcome in effectiveness [18].

The basic assumption carried on routing area as follows:

The MFO (Moth Flame Optimization) algorithm is interpreted as  $MFO = \{L, N, T\}$

- The starting point of departure
- The ending point of arrival
- The variation occurred during the route if possible path is considered [15].

Where, L represents the total population in the location taken into consideration. N implies the number of population in the area of vehicle presence. T indicates the population amount on the area.

The fitness function of MFO is expressed as

$$F(S) = R(S) +$$

Where, R(S) refers to the resource needed for route such as fuel usage, number of vehicle etc. It should be cost effective in nature. [15] There are 4 cases considered such as C1(S) for cost for not considering the capacity of route. C2(S) implies that the duration gets increases due to longer route. C3(S) indicates for not considering the duration limits. C4(S) represents not considering the demand balance. represents the coefficient of every cost.

#### 5.1 Methodology

While considering the trash collection in a locality, there will be numerous places available to manage the disposal. There are many operations assumed namely, traffic problem will be raised when

taking account of original route of the vehicle and when no node terminals are available for the disposal of garbage. This case becomes worse when the vehicle loads full and it will spill out if overloaded. In this there will be number of node terminals available for disposing their trashes. Assume the second case, the terminals available in one route will be high and the intermediate station is low rather than the optional route considered. In this scenario, the vehicle for disposal of garbage will consider the larger intermediate station route because it is of quite easier than the smaller intermediate station.

Consider next case that is two optional routes if the locating terminals are higher in one path and the locating terminals are smaller in another path. In this case, the vehicle will finds the track of larger neighbouring terminals because it will collect all the trashes from the same way it considers. It is reliable than the way that possess the smaller amount of locating nodes. Because at the one travel, all the nodes garbage are collected. Assume the next case that the vehicle has the choice to cross over from one route to another if it finds any complexities on the following route. Hence it reduces the complexity on the appropriate route. The cross over takes place when the man collecting the trashes finds easier in function. After neglecting all the choices, relocation takes place by eliminating all the unwanted node terminals.

The travel of separate collection of node will be considered as combined manner, so that the distance also gets reduced and node terminals are also decreased. The condition will be considered in the case, as the number of node terminals is high the intermediate station for collecting the garbage also is high; hence this is efficient for garbage disposing. For this decision handling, moth flame optimization algorithm is used and best-case criteria are used based on the decision.

Assume that there are various collection strategies; the vehicle initially considers the way of collecting the garbage. If the node is present on the route the vehicle collects the garbage. Either if it is absence then the vehicle will find next neighbouring nodes. When the vehicle gets full loaded it gets disposed on the intermediate station and another container is used for the collection. If the intermediate station is not present, then the garbage gets spill out when gets reloaded. Hence the purpose of the station is helpful in the need of full of garbage. Hence moth flame optimization is helpful in collecting garbage in cost effective manner and this provokes a good way of promoting smart city collection.

As a scenario, consider a metropolitan city there consists of numerous populations present and hence the garbage produced also gets increased. There each house and each street promotes large amount of garbage. Earlier and present algorithm for the optimization of collecting garbage is not so effective in all consequences. Because it requires separate stages for each updating criteria and fixation values. MFO promotes in a combined manner with the advantageous of efficiency by all the resources handled. It does all process in the same cycle with the outcome as effective. When a street named A is commenced for collecting the garbage there exists many nodes for disposal of their household trashes [10]. For visiting the entire node in the particular locality, a clear view of the nodes will be seen to determine the exact shortest route. When it is determined it is easy for the collection of waste to be maintained in appropriate manner without any dislocation.

### **5.1.2 Roll on Roll Off strategy:**

It is defined as the inclusion of usage of large containers for the collection of garbage in continuous rotation. It is considered as the regular waste collect by using vehicle. It is also called as one

step skip collection strategy because if the demand of one customer increases integrally, the priority gets enhanced. It is solved by using multiple bound methods with heuristic algorithms.

#### Algorithm 1: Process of Function

- Begin the procedure using moth flies;
- repeat
- locate the appropriate nearest node
- Collect the trash
- Move to the next neighbouring node
- If it is absent, update the position with respect to nearest node
- If the garbage vehicle gets full
- Find out the intermediate station for disposing
  - Depends upon the time management
- it move further to the next nodes
  - end if
  - Process continues until all the garbage gets collected
  - end

This algorithm is cost effective because it reduces the vehicle usage, hence fuel consumption gets reduced automatically and time management. It promotes by initiate the routing by finding the shortest path, between the depot and the final destination. It visits all the terminals available on the route. If none terminals is present in the taken route means, location of different route is handled by updating the fitness value. And numbers of operations are handled like crossover, relocation, optional route based on the fitness value. When the vehicle gets full, then it disposed all the garbage on the intermediate stage or take different container from the station by leaving the fully loaded container to reduce them time usage. With the time given, the allotted places are get visited appropriately

The routing cost gets increases due to the long span of travelling for every collection of trashes. It took large duration for each collection without any intermediate station [4] for disposing when the vehicle gets full. But using proposed system, there is a station for locating the available garbage and it possess better results in consuming time to proceed for the further stations.

#### 5.1.3 Advantages over existing system

Moth flame Optimization possesses certain advantages over the existing approach. It describes as follows

- It promotes cost reduction in all the resources that are needed for the disposal of garbage.
- It finds best route to the departure for disposing
- The availability of intermediate station if requisite is the basic foundation for this approach.
- The distance, vehicle volume to the garbage finds convenience by providing neighbouring nodes.

It is sure that this algorithm will promote a best smart city in future development.

## 6. Conclusion:

It promotes a single procedure that includes the Tabu criteria and updation in a combined manner. It is simple to implement and cost effective in nature. It reduces all the necessary resources required for the execution. It reduces the span between the first and end node [4], by evaluating shortest distance. Hence by concluding that through this optimization, the cost required for removal of trashes is improved and it proves that the algorithm provides enhancement to other existing systems. It is well applicable for practical case scenarios. It possesses intermediate station for the availability of the garbage to proceed to the next neighbouring localized places; hence it reduces the distance and cost of the consumption [19]. It produces best results for various problems towards cost enhancement, high complex nature and discrete promotions.

## 7. References:

- [1] Ahn, C.W. and Ramakrishna, R.S., 2002. A genetic algorithm for shortest path routing problem and the sizing of populations. *IEEE transactions on evolutionary computation*, 6(6), pp.566-579.
- [2] Al Salami, N.M., 2009. Ant colony optimization algorithm. *UbiCC Journal*, 4(3), pp.823-826.
- [3] Bahrami, M., Bozorg-Haddad, O. and Chu, X., 2018. Moth-Flame Optimization (MFO) Algorithm. In *Advanced Optimization by Nature-Inspired Algorithms*, Springer, Singapore, pp.131-141
- [4] Buhrkal, K., Larsen, A. and Ropke, S., 2012. The waste collection vehicle routing problem with time windows in a city logistics context. *Procedia-Social and Behavioral Sciences*, 39, pp.241-254.
- [5] Chalkias, C. and Lasaridi, K., 2009. A GIS based model for the optimisation of municipal solid waste collection the case study of Nikea, Athens, Greece. *technology*, pp.11-15.
- [6] Eisted, R., Larsen, A.W. and Christensen, T.H., 2009. Collection, transfer and transport of waste accounting of greenhouse gases and global warming contribution. *Waste Management & Research*, 27(8), pp.738-745.
- [7] Garg, P. and Gupta, A., 2017. Optimized open shortest path first algorithm based on moth flame optimization. *Indian Journal of Science and Technology*, 9(48).
- [8] Gendreau, M., Hertz, A. and Laporte, G., 1994. A tabu search heuristic for the vehicle routing problem, *Management science*, 40(10), pp.1276-1290.
- [9] Ghose, M.K., Dikshit, A.K. and Sharma, S.K., 2006. A GIS based transportation model for solid waste disposal—A case study on Asansol municipality. *Waste management*, 26(11), pp.1287-1293.
- [10] Iriarte, A., Gabarrell, X. and Rieradevall, J., 2009. LCA of selective waste collection systems in dense urban areas. *Waste Management*, 29(2), pp.903-914.
- [11] Karadimas, N.V., Papatzelou, K. and Loumos, V.G., 2007. Optimal solid waste collection routes identified by the ant colony system algorithm. *Waste management & research*, 25(2), pp.139-147.
- [12] Kennedy, J., 2011. Particle swarm optimization. In *Encyclopedia of machine learning*, Springer, Boston, MA, pp.760-766.



- [13] Larsen, A.W., Vrgoc, M., Christensen, T.H. and Lieberknecht, P., 2009. Diesel consumption in waste collection and transport and its environmental significance. *Waste Management & Research*, 27(7), pp.652-659.
- [14] McLeod, F. and Cherrett, T., 2008. Quantifying the transport impacts of domestic waste collection strategies. *Waste Management*, 28(11), pp.2271-2278.
- [15] Mirjalili, S., 2015. Moth-flame optimization algorithm A novel nature-inspired heuristic paradigm. *Knowledge-Based Systems*, 89, pp.228-249.
- [16] Mohanty, B., 2018. Performance analysis of moth flame optimization algorithm for AGC system. *International Journal of Modelling and Simulation*, pp.1-15.
- [17] Noto, M. and Sato, H., 2000. A method for the shortest path search by extended Dijkstra algorithm. In *Systems, Man, and Cybernetics, 2000 IEEE International Conference on* Vol. 3, pp. 2316-2320.
- [18] Nuortio, T., Kytöjoki, J., Niska, H. and Bräysy, O., 2006. Improved route planning and scheduling of waste collection and transport. *Expert systems with applications*, 30(2), pp.223-232.
- [19] Quagliarella, D. ed., 1998. *Genetic algorithms and evolution strategy in engineering and computer science recent advances and industrial applications*. Chichester Wiley.
- [20] Rana, S., Singhm, R. and Rattan, M., 2016. Optimization applications using MFO algorithm a review. *Int. J. Eng. Appl. Sci. Technol*, 2(1), pp.54-56.
- [21] Rajeswari, M., Amudhavel, J. and Dhavachelvan, P., 2017. Moth-flame algorithm for solving coverage problem in wireless sensor network. *advances and applications in mathematical sciences*, 17(1), pp.51-64.
- [22] Yamany, W., Fawzy, M., Tharwat, A. and Hassanien, A.E., 2015, December. Moth-flame optimization for training multi-layer perceptrons. In *Computer Engineering Conference (ICENCO), 2015*, pp. 267-272.